

Trimble Ri

Robotic Total Station



Key Features

- Level Detection & Monitoring
- Built-in calibration
- Focusing Red Laser EDM
- Trimble Vision technology
- Upgradeable Instrument
- FieldLink Integration

Total Performance

Expanded range and various zoom levels plus new side to side search pattern for quick-lock onto prism, saves time when searching for a target.

Built for Construction

Trimble's most scalable, accurate and automated Robotic Total Station. Easy set-up for faster efficient positioning with minimal training required.

The Trimble Ri is part of the Trimble Portfolio of Building Construction products advancing mixed reality technology through data visualization in the field.

Leverage the XR10 with HoloLens 2, together with FieldLink MR, to view and measure with confidence and precision.



Trimble Ri Robotic Total Station

Performance

Accuracy
 Angle Accuracy
 (based on ISO 17123-3) **2" (0.6 mgon) / 3" (0.9 mgon)**

Automatic level compensator
 Type **MEMS, dual-axis, self-leveling**
 Accuracy **2" (0.6 mgon)**
 Working Range **± 5 gon (± 4.5 °)**

Distance measurement
 Accuracy to Reflectors (based on ISO 17123-4)
 Standard **2 mm (0.007 ft) + 2 ppm**
 Tracking **3 mm (0.01 ft)**
 Accuracy Reflectorless Mode **2 mm (0.007 ft) + 2 ppm**
 Range Reflector Mode
 Single Prism 50 mm **900 m (2953 ft)**
 Single Prism 25 mm **400 m (1312 ft)**
 Cat-Eye Reflector 85 mm **300 m (984 ft)**
 Foil Reflector 60 mm **300 m (984 ft)**
 Shortest possible range **1 m (3.3 ft)**
 Range Reflectorless Mode
 Kodak White (90% reflective) **840 m (2756 ft) / 150 m (492 ft)**
 Kodak Gray Card (18% reflective) **375 m (1230 ft) / 150 m (492ft)**
 Shortest possible range **0.5 m (1.6 ft)**

Robotic Tracking
 360° Cat-Eye Prism
 Robotic Range **1,5 m (5 ft) ... 120 m (427 ft)**
 360° Prism
 Robotic Range **1,5 m (5 ft) ... 400 m (985 ft)**

EDM Specifications

EDM Laser and Principle
 Light source **Laser Diode 660 nm**
 Laser Class Safety
 Reflector Mode **Laser Class 2**
 Reflector-less Mode and Laser Pointer **Laser Class 2**

EDM Beam divergence
 Divergence **adaptive to distance (focusable laser)**

EDM Specifications cont'd

Diameter **< 10 mm @ 100 m (0.4 in/328 ft)**
 Diameter **< 4 mm @ 40 m (0.16 in/131 ft)**

General Specifications

Telescope
 Lens System **Continuous focus**
 Aperture **32 mm (1.3 in)**
 Field of view **2 gon – 12 gon (1.8 deg – 11 deg)**
 Focusing distance **0.5 m – Infinity (1.7 ft – Infinity)**
 Crosshair **Digital, superimposed**
 Tracklight built in **Red / Green Status LEDs**

Camera
 Resolution of Stream **960 x 540 or 1920 x 1080**
 Resolution of Still Image **1 - 7 m: 1920 x 1080 (2,1 MPx)
 7 - 300 m: 2560 x 1440 (3,7 MPx)**

Environmental
 Operating temperature **-20 °C to +50 °C (-4 °F to +122 °F)**
 Storage temperature **-40 °C to +70 °C (-40°F to +158 °F)**
 Dust and water proofing **IP55**

Power Supply
 Internal battery **Li-Ion, 10.8 V / 6.5Ah**
 Operating time **4.5 hours**

Communications
 Wireless communication **WLAN, Dual 2.4GHz and 5GHz band,
 IEEE 802.11 a/b/g/n/ac**

Weight
 Instrument (Trimble Ri) **5,65 kg**
 Internal battery (Trimble Ri) **0.37 kg**

Dimensions
 Height x Width x Depth (Trimble Ri) **368mm x 184mm x 178mm**



UPLOAD
DEALER LOGO

UPLOAD
TRIMBLE AUTHORIZED
DEALER LOGO

Trimble Building Construction Field Solutions
 10368 Westmoor Drive
 Westminster CO 80021 USA
 800-361-1249 (Toll Free)
 +1-937-245-5154 Phone
 fieldtech@construction.trimble.com

